

Snow Melt Mats



SCM Series Snow Melt Mat is designed for melting snow and ice for improved safety conditions.

SCM Snow Melt 208V Mat Features

- 20 Ft. Cold Lead, for use in concrete, asphalt & under pavers
- Single point connection, 10 year warranty
- Use in sidewalks, driveways, stairs, ramps, etc.
- Tefzel® Insulation, TPU Jacket, Emits zero EMFs



Model Code:

SCM	20	48	24	-5
A	B	C	D	E
A: Snow Melt Mat				
B: 20 - 208V				
24 - 240V				
48 - 480V				
C: Watts per Sq/Ft				
D: Width of Mat				
E: Mat Length				

24" 208V

MODEL (24" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (3" SPACING)	WATTS (48 W/FT²)	AMPS
SCM204824-4	42032	4.4 FT.	8.8 SQ. FT.	422	2.0
SCM204824-6	42033	6.3 FT.	12.5 SQ. FT.	600	2.9
SCM204824-8	42034	8.8 FT.	17.5 SQ. FT.	840	4.0
SCM204824-10	42035	10.6 FT.	21.3 SQ. FT.	1022	4.9
SCM204824-13	42036	13.1 FT.	26.3 SQ. FT.	1262	6.1
SCM204824-15	42037	15.6 FT.	31.3 SQ. FT.	1502	7.2
SCM204824-18	42038	18.1 FT.	36.3 SQ. FT.	1742	8.4
SCM204824-20	42039	20.0 FT.	40.0 SQ. FT.	1920	9.2
SCM204824-22	42040	22.5 FT.	45.0 SQ. FT.	2160	10.4
SCM204824-26	42041	26.3 FT.	52.5 SQ. FT.	2520	12.1
SCM204824-30	42042	30.6 FT.	61.3 SQ. FT.	2942	14.1
SCM204824-35	42043	35.0 FT.	70.0 SQ. FT.	3360	16.2
SCM204824-40	42044	40.0 FT.	80.0 SQ. FT.	3840	18.5
SCM204824-44	42045	44.4 FT.	88.8 SQ. FT.	4262	20.5
SCM204824-51	42046	51.3 FT.	102.5 SQ. FT.	4920	23.7
SCM204824-57	42047	57.5 FT.	115.0 SQ. FT.	5520	26.5

MODEL (24" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (4" SPACING)	WATTS (36 W/FT²)	AMPS
SCM203624-5	42048	5.8 FT.	11.7 SQ. FT.	422	2.0
SCM203624-8	42049	8.3 FT.	16.7 SQ. FT.	600	2.9
SCM203624-11	42050	11.7 FT.	23.3 SQ. FT.	840	4.0
SCM203624-14	42051	14.2 FT.	28.3 SQ. FT.	1022	4.9
SCM203624-17	42052	17.5 FT.	35.0 SQ. FT.	1262	6.1
SCM203624-20	42053	20.8 FT.	41.7 SQ. FT.	1502	7.2
SCM203624-24	42054	24.2 FT.	48.3 SQ. FT.	1742	8.4
SCM203624-26	42055	26.7 FT.	53.3 SQ. FT.	1920	9.2
SCM203624-30	42056	30.0 FT.	60.0 SQ. FT.	2160	10.4
SCM203624-35	42057	35.0 FT.	70.0 SQ. FT.	2520	12.1
SCM203624-40	42058	40.8 FT.	81.7 SQ. FT.	2942	14.1
SCM203624-46	42059	46.7 FT.	93.3 SQ. FT.	3360	16.2
SCM203624-53	42060	53.3 FT.	106.7 SQ. FT.	3840	18.5
SCM203624-59	42061	59.2 FT.	118.3 SQ. FT.	4262	20.5
SCM203624-68	42062	68.3 FT.	136.7 SQ. FT.	4920	23.7
SCM203624-76	42063	76.7 FT.	153.3 SQ. FT.	5520	26.5

30" 208V

MODEL (30" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (3" SPACING)	WATTS (48 W/FT²)	AMPS
SCM204830-3	42064	3.5 FT.	8.8 SQ. FT.	560	2.0
SCM204830-5	42065	5.0 FT.	12.5 SQ. FT.	800	2.9
SCM204830-7	42066	7.0 FT.	17.5 SQ. FT.	1120	4.0
SCM204830-8	42067	8.5 FT.	21.3 SQ. FT.	1360	4.9
SCM204830-10	42068	10.5 FT.	26.3 SQ. FT.	1680	6.1
SCM204830-12	42069	12.5 FT.	31.3 SQ. FT.	2000	7.2
SCM204830-14	42070	14.5 FT.	36.3 SQ. FT.	2320	8.4
SCM204830-16	42071	16.0 FT.	40.0 SQ. FT.	2560	9.2
SCM204830-18	42072	18.0 FT.	45.0 SQ. FT.	2880	10.4
SCM204830-21	42073	21.0 FT.	52.5 SQ. FT.	3360	12.1
SCM204830-24	42074	24.5 FT.	61.3 SQ. FT.	3920	14.1
SCM204830-28	42075	28.0 FT.	70.0 SQ. FT.	4480	16.2
SCM204830-32	42076	32.0 FT.	80.0 SQ. FT.	5120	18.5
SCM204830-35	42077	35.5 FT.	88.8 SQ. FT.	5680	20.5
SCM204830-41	42078	41.0 FT.	102.5 SQ. FT.	6560	23.7
SCM204830-46	42079	46.0 FT.	115.0 SQ. FT.	7360	26.5

MODEL (30" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (4" SPACING)	WATTS (36 W/FT²)	AMPS
SCM203630-4	42080	4.7 FT.	11.7 SQ. FT.	420	2.0
SCM203630-6	42081	6.7 FT.	16.7 SQ. FT.	600	2.9
SCM203630-9	42082	9.3 FT.	23.3 SQ. FT.	840	4.0
SCM203630-11	42083	11.3 FT.	28.3 SQ. FT.	1020	4.9
SCM203630-14	42084	14.0 FT.	35.0 SQ. FT.	1260	6.1
SCM203630-16	42085	16.7 FT.	41.7 SQ. FT.	1500	7.2
SCM203630-19	42086	19.3 FT.	48.3 SQ. FT.	1740	8.4
SCM203630-21	42087	21.3 FT.	53.3 SQ. FT.	1920	9.2
SCM203630-24	42088	24.0 FT.	60.0 SQ. FT.	2160	10.4
SCM203630-28	42089	28.0 FT.	70.0 SQ. FT.	2520	12.1
SCM203630-32	42090	32.7 FT.	81.7 SQ. FT.	2940	14.1
SCM203630-37	42091	37.3 FT.	93.3 SQ. FT.	3360	16.2
SCM203630-42	42092	42.7 FT.	106.7 SQ. FT.	3840	18.5
SCM203630-47	42093	47.3 FT.	118.3 SQ. FT.	4260	20.5
SCM203630-54	42094	54.7 FT.	136.7 SQ. FT.	4920	23.7
SCM203630-61	42095	61.3 FT.	153.3 SQ. FT.	5520	26.5

36" 208V

MODEL (36" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (3" SPACING)	WATTS (48 W/FT²)	AMPS
SCM204836-2	42096	2.9 FT.	8.8 SQ. FT.	420	2.0
SCM204836-4	42097	4.2 FT.	12.5 SQ. FT.	600	2.9
SCM204836-5	42098	5.8 FT.	17.5 SQ. FT.	840	4.0
SCM204836-7	42099	7.1 FT.	21.3 SQ. FT.	1020	4.9
SCM204836-8	42100	8.8 FT.	26.3 SQ. FT.	1260	6.1
SCM204836-10	42101	10.4 FT.	31.3 SQ. FT.	1500	7.2
SCM204836-12	42102	12.1 FT.	36.3 SQ. FT.	1740	8.4
SCM204836-13	42103	13.3 FT.	40.0 SQ. FT.	1920	9.2
SCM204836-15	42104	15.0 FT.	45.0 SQ. FT.	2160	10.4
SCM204836-17	42105	17.5 FT.	52.5 SQ. FT.	2520	12.1
SCM204836-20	42106	20.4 FT.	61.3 SQ. FT.	2940	14.1
SCM204836-23	42107	23.3 FT.	70.0 SQ. FT.	3360	16.2
SCM204836-26	42108	26.7 FT.	80.0 SQ. FT.	3840	18.5
SCM204836-29	42109	29.6 FT.	88.8 SQ. FT.	4260	20.5
SCM204836-34	42110	34.2 FT.	102.5 SQ. FT.	4920	23.7
SCM204836-38	42111	38.3 FT.	115.0 SQ. FT.	5520	26.5

MODEL (36" WIDE)	UPC (093319)	MAT LENGTH	HEATED AREA (4" SPACING)	WATTS (36 W/FT²)	AMPS
SCM203636-3	42112	3.9 FT.	11.7 SQ. FT.	420	2.0
SCM203636-5	42113	5.6 FT.	16.7 SQ. FT.	600	2.9
SCM203636-7	42114	7.8 FT.	23.3 SQ. FT.	840	4.0
SCM203636-9	42115	9.4 FT.	28.3 SQ. FT.	1020	4.9
SCM203636-11	42116	11.7 FT.	35.0 SQ. FT.	1260	6.1
SCM203636-13	42117	13.9 FT.	41.7 SQ. FT.	1500	7.2
SCM203636-16	42118	16.1 FT.	48.3 SQ. FT.	1740	8.4
SCM203636-17	42119	17.8 FT.	53.3 SQ. FT.	1920	9.2
SCM203636-20	42120	20.0 FT.	60.0 SQ. FT.	2160	10.4
SCM203636-23	42121	23.3 FT.	70.0 SQ. FT.	2520	12.1
SCM203636-27	42122	27.2 FT.	81.7 SQ. FT.	2940	14.1
SCM203636-31	42123	31.1 FT.	93.3 SQ. FT.	3360	16.2
SCM203636-35	42124	35.6 FT.	106.7 SQ. FT.	3840	18.5
SCM203636-39	42125	39.4 FT.	118.3 SQ. FT.	4260	20.5
SCM203636-45	42126	45.6 FT.	136.7 SQ. FT.	4920	23.7
SCM203636-51	42127	51.1 FT.	153.3 SQ. FT.	5520	26.5

Snow Melt Mats



Model Code:

SCM	20	48	24	-5
A	B	C	D	E
A: Snow Melt Mat				
B: 20 - 208V				
24 - 240V				
48 - 480V				
C: Watts per Sq/Ft				
D: Width of Mat				
E: Mat Length				

SCM Series Snow Melt Mat is designed for melting snow and ice for improved safety conditions.

SCM Snow Melt 240V Mat Features

- 20 Ft. Cold Lead, for use in concrete, asphalt & under pavers
- 10 year warranty, Emits zero EMFs (electromagnetic fields)
- Use in sidewalks, driveways, stairs, ramps, etc.
- Single point connection, Tefzel® Insulation, TPU Jacket

	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS	
	(24" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(24" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
24" 240V	SCM244824-5	42128	5.0 FT.	10.0 SQ. FT.	480	2.0	SCM243624-6	42144	6.7 FT.	13.3 SQ. FT.	478	2.0
	SCM244824-7	42129	7.5 FT.	15.0 SQ. FT.	720	3.0	SCM243624-10	42145	10.0 FT.	20.0 SQ. FT.	720	3.0
	SCM244824-10	42130	10.0 FT.	20.0 SQ. FT.	960	4.0	SCM243624-13	42146	13.3 FT.	26.7 SQ. FT.	961	4.0
	SCM244824-12	42131	12.5 FT.	25.0 SQ. FT.	1200	5.0	SCM243624-16	42147	16.7 FT.	33.3 SQ. FT.	1198	5.0
	SCM244824-15	42132	15.0 FT.	30.0 SQ. FT.	1440	6.0	SCM243624-20	42148	20.0 FT.	40.0 SQ. FT.	1440	6.0
	SCM244824-18	42133	18.1 FT.	36.3 SQ. FT.	1742	7.3	SCM243624-24	42149	24.2 FT.	48.3 SQ. FT.	1738	7.3
	SCM244824-20	42134	20.6 FT.	41.3 SQ. FT.	1982	8.3	SCM243624-27	42150	27.5 FT.	55.0 SQ. FT.	1980	8.3
	SCM244824-23	42135	23.1 FT.	46.3 SQ. FT.	2222	9.3	SCM243624-30	42151	30.8 FT.	61.7 SQ. FT.	2221	9.3
	SCM244824-25	42136	25.6 FT.	51.3 SQ. FT.	2462	10.3	SCM243624-34	42152	34.2 FT.	68.3 SQ. FT.	2458	10.3
	SCM244824-30	42137	30.6 FT.	61.3 SQ. FT.	2942	12.3	SCM243624-40	42153	40.8 FT.	81.7 SQ. FT.	2941	12.3
	SCM244824-35	42138	35.6 FT.	71.3 SQ. FT.	3422	14.3	SCM243624-47	42154	47.5 FT.	95.0 SQ. FT.	3420	14.3
	SCM244824-40	42139	40.6 FT.	81.3 SQ. FT.	3902	16.3	SCM243624-54	42155	54.2 FT.	108.3 SQ. FT.	3898	16.3
	SCM244824-46	42140	46.3 FT.	92.5 SQ. FT.	4440	18.5	SCM243624-61	42156	61.7 FT.	123.3 SQ. FT.	4438	18.5
	SCM244824-51	42141	51.3 FT.	102.5 SQ. FT.	4920	20.5	SCM243624-68	42157	68.3 FT.	136.7 SQ. FT.	4921	20.5
SCM244824-59	42142	59.4 FT.	118.8 SQ. FT.	5702	23.8	SCM243624-79	42158	79.2 FT.	158.3 SQ. FT.	5698	23.8	
SCM244824-66	42143	66.9 FT.	133.8 SQ. FT.	6422	26.8	SCM243624-89	42159	89.2 FT.	178.3 SQ. FT.	6418	26.8	
30" 240V	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS	
	(30" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(30" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
	SCM244830-4	42160	4.0 FT.	10.0 SQ. FT.	480	2.0	SCM243630-5	42176	5.3 FT.	13.3 SQ. FT.	480	2.0
	SCM244830-6	42161	6.0 FT.	15.0 SQ. FT.	720	3.0	SCM243630-8	42177	8.0 FT.	20.0 SQ. FT.	720	3.0
	SCM244830-8	42162	8.0 FT.	20.0 SQ. FT.	960	4.0	SCM243630-10	42178	10.7 FT.	26.7 SQ. FT.	960	4.0
	SCM244830-10	42163	10.0 FT.	25.0 SQ. FT.	1200	5.0	SCM243630-13	42179	13.3 FT.	33.3 SQ. FT.	1200	5.0
	SCM244830-12	42164	12.0 FT.	30.0 SQ. FT.	1440	6.0	SCM243630-16	42180	16.0 FT.	40.0 SQ. FT.	1440	6.0
	SCM244830-14	42165	14.5 FT.	36.3 SQ. FT.	1740	7.3	SCM243630-19	42181	19.3 FT.	48.3 SQ. FT.	1740	7.3
	SCM244830-16	42166	16.5 FT.	41.3 SQ. FT.	1980	8.3	SCM243630-22	42182	22.0 FT.	55.0 SQ. FT.	1980	8.3
	SCM244830-18	42167	18.5 FT.	46.3 SQ. FT.	2220	9.3	SCM243630-24	42183	24.7 FT.	61.7 SQ. FT.	2220	9.3
	SCM244830-20	42168	20.5 FT.	51.3 SQ. FT.	2460	10.3	SCM243630-27	42184	27.3 FT.	68.3 SQ. FT.	2460	10.3
	SCM244830-24	42169	24.5 FT.	61.3 SQ. FT.	2940	12.3	SCM243630-32	42185	32.7 FT.	81.7 SQ. FT.	2940	12.3
	SCM244830-28	42170	28.5 FT.	71.3 SQ. FT.	3420	14.3	SCM243630-38	42186	38.0 FT.	95.0 SQ. FT.	3420	14.3
	SCM244830-32	42171	32.5 FT.	81.3 SQ. FT.	3900	16.3	SCM243630-43	42187	43.3 FT.	108.3 SQ. FT.	3900	16.3
SCM244830-37	42172	37.0 FT.	92.5 SQ. FT.	4440	18.5	SCM243630-49	42188	49.3 FT.	123.3 SQ. FT.	4440	18.5	
SCM244830-41	42173	41.0 FT.	102.5 SQ. FT.	4920	20.5	SCM243630-54	42189	54.7 FT.	136.7 SQ. FT.	4920	20.5	
SCM244830-47	42174	47.5 FT.	118.8 SQ. FT.	5700	23.8	SCM243630-69	42190	63.3 FT.	158.3 SQ. FT.	5700	23.8	
SCM244830-53	42175	53.5 FT.	133.8 SQ. FT.	6420	26.8	SCM243630-71	42191	71.3 FT.	178.3 SQ. FT.	6420	26.8	
36" 240V	MODEL	UPC	MAT	HEATED AREA	WATTS		MODEL	UPC	MAT	HEATED AREA	WATTS	
	(36" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)		AMPS	(36" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
	SCM244836-3	42192	3.3 FT.	10.0 SQ. FT.	480	2.0	SCM243636-4	42208	4.4 FT.	13.3 SQ. FT.	480	2.0
	SCM244836-5	42193	5.0 FT.	15.0 SQ. FT.	720	3.0	SCM243636-6	42209	6.7 FT.	20.0 SQ. FT.	720	3.0
	SCM244836-6	42194	6.7 FT.	20.0 SQ. FT.	960	4.0	SCM243636-8	42210	8.9 FT.	26.7 SQ. FT.	960	4.0
	SCM244836-8	42195	8.3 FT.	25.0 SQ. FT.	1200	5.0	SCM243636-11	42211	11.1 FT.	33.3 SQ. FT.	1200	5.0
	SCM244836-10	42196	10.0 FT.	30.0 SQ. FT.	1440	6.0	SCM243636-13	42212	13.3 FT.	40.0 SQ. FT.	1440	6.0
	SCM244836-12	42197	12.1 FT.	36.3 SQ. FT.	1740	7.3	SCM243636-16	42213	16.1 FT.	48.3 SQ. FT.	1740	7.3
	SCM244836-13	42198	13.8 FT.	41.3 SQ. FT.	1980	8.3	SCM243636-18	42214	18.3 FT.	55.0 SQ. FT.	1980	8.3
	SCM244836-15	42199	15.4 FT.	46.3 SQ. FT.	2220	9.3	SCM243636-20	42215	20.6 FT.	61.7 SQ. FT.	2220	9.3
	SCM244836-17	42200	17.1 FT.	51.3 SQ. FT.	2460	10.3	SCM243636-22	42216	22.8 FT.	68.3 SQ. FT.	2460	10.3
	SCM244836-20	42201	20.4 FT.	61.3 SQ. FT.	2940	12.3	SCM243636-27	42217	27.2 FT.	81.7 SQ. FT.	2940	12.3
	SCM244836-23	42202	23.8 FT.	71.3 SQ. FT.	3420	14.3	SCM243636-31	42218	31.7 FT.	95.0 SQ. FT.	3420	14.3
	SCM244836-27	42203	27.1 FT.	81.3 SQ. FT.	3900	16.3	SCM243636-36	42219	36.1 FT.	108.3 SQ. FT.	3900	16.3
SCM244836-30	42204	30.8 FT.	92.5 SQ. FT.	4440	18.5	SCM243636-41	42220	41.1 FT.	123.3 SQ. FT.	4440	18.5	
SCM244836-34	42205	34.2 FT.	102.5 SQ. FT.	4920	20.5	SCM243636-45	42221	45.6 FT.	136.7 SQ. FT.	4920	20.5	
SCM244836-39	42206	39.6 FT.	118.8 SQ. FT.	5700	23.8	SCM243636-52	42222	52.8 FT.	158.3 SQ. FT.	5700	23.8	
SCM244836-44	42207	44.6 FT.	133.8 SQ. FT.	6420	26.8	SCM243636-59	42223	59.4 FT.	178.3 SQ. FT.	6420	26.8	

Snow Melt Mats



Model Code:

SCM	20	48	24	-5
A	B	C	D	E

A: Snow Melt Mat
B: 20 - 208V
24 - 240V
48 - 480V
C: Watts per Sq/Ft
D: Width of Mat
E: Mat Length



SCM Series Snow Melt Mat is designed for melting snow and ice for improved safety conditions.

SCM Snow Melt 480V Mat Features

- 20 Ft. Cold Lead, for use in concrete, asphalt & under pavers
- 10 year warranty, Emits zero EMFs (electromagnetic fields)
- Use in sidewalks, driveways, stairs, ramps, etc.
- Single point connection, Tefzel® Insulation, TPU Jacket

	MODEL	UPC	MAT	HEATED AREA	WATTS	MODEL	UPC	MAT	HEATED AREA	WATTS
	(24" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)	(24" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
24" 480V	SCM484824-10	42448	10.0 FT.	20.0 SQ. FT.	960	SCM483624-13	42427	13.3 FT.	26.7 SQ. FT.	961
	SCM484824-25	42449	25.0 FT.	50.0 SQ. FT.	2400	SCM483624-33	42428	33.3 FT.	66.7 SQ. FT.	2401
	SCM484824-41	42450	41.3 FT.	82.5 SQ. FT.	3960	SCM483624-55	42429	55.0 FT.	110.0 SQ. FT.	3960
	SCM484824-61	42451	61.3 FT.	122.5 SQ. FT.	5880	SCM483624-81	42430	81.7 FT.	163.3 SQ. FT.	5878
	SCM484824-91	42452	91.9 FT.	183.8 SQ. FT.	8822	SCM483624-122	42431	122.5 FT.	245.0 SQ. FT.	8820
	SCM484824-102	42453	102.5 FT.	205.0 SQ. FT.	9840	SCM483624-136	42432	136.7 FT.	273.3 SQ. FT.	9838
	SCM484824-117	42454	117.5 FT.	235.0 SQ. FT.	11280	SCM483624-156	42433	156.7 FT.	313.3 SQ. FT.	11278
30" 480V	MODEL	UPC	MAT	HEATED AREA	WATTS	MODEL	UPC	MAT	HEATED AREA	WATTS
	(30" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)	(30" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
	SCM484830-82	42455	8.0 FT.	20.0 SQ. FT.	960	SCM483630-10	42434	10.7 FT.	26.7 SQ. FT.	961
	SCM484830-20	42456	20.0 FT.	50.0 SQ. FT.	2400	SCM483630-26	42435	26.7 FT.	66.7 SQ. FT.	2401
	SCM484830-33	42457	33.0 FT.	82.5 SQ. FT.	3960	SCM483630-44	42436	44.0 FT.	110.0 SQ. FT.	3960
	SCM484830-49	42458	49.0 FT.	122.5 SQ. FT.	5880	SCM483630-65	42437	65.3 FT.	163.3 SQ. FT.	5878
	SCM484830-73	42459	73.0 FT.	183.8 SQ. FT.	8822	SCM483630-98	42438	98.0 FT.	245.0 SQ. FT.	8820
SCM484830-82	42160	82.0 FT.	205.0 SQ. FT.	9840	SCM483630-109	42439	109.3 FT.	273.3 SQ. FT.	9838	
SCM484830-94	42461	94.0 FT.	235.0 SQ. FT.	11280	SCM483630-125	42440	125.3 FT.	313.3 SQ. FT.	11278	
36" 480V	MODEL	UPC	MAT	HEATED AREA	WATTS	MODEL	UPC	MAT	HEATED AREA	WATTS
	(36" WIDE)	(093319)	LENGTH	(3" SPACING)	(48 W/FT²)	(36" WIDE)	(093319)	LENGTH	(4" SPACING)	(36 W/FT²)
	SCM484836-6	42462	6.7 FT.	20.0 SQ. FT.	960	SCM483636-8	42441	8.9 FT.	26.7 SQ. FT.	961
	SCM484836-16	42463	16.7 FT.	50.0 SQ. FT.	2400	SCM483636-22	42442	22.2 FT.	66.7 SQ. FT.	2401
	SCM484836-27	42464	27.5 FT.	82.5 SQ. FT.	3960	SCM483636-36	42443	36.7 FT.	110.0 SQ. FT.	3960
	SCM484836-40	42465	40.8 FT.	122.5 SQ. FT.	5880	SCM483636-54	42444	54.4 FT.	163.3 SQ. FT.	5878
	SCM484836-61	42466	61.3 FT.	183.8 SQ. FT.	8822	SCM483636-81	42445	81.7 FT.	245.0 SQ. FT.	8820
SCM484836-68	42467	68.3 FT.	205.0 SQ. FT.	9840	SCM483636-91	42446	91.1 FT.	273.3 SQ. FT.	9838	
SCM484836-78	42468	78.3 FT.	235.0 SQ. FT.	11280	SCM483636-104	42447	104.4 FT.	313.3 SQ. FT.	11278	

More voltages available. Call for additional information

****Controls and thermostats should always be used with King heating cable systems.**