



9131 10th Ave. South, Seattle, WA 98108 | [www.king-electric.com](http://www.king-electric.com)

|          |                |
|----------|----------------|
| Date:    | Contact Name:  |
| Company: | Contact Phone: |
| Job:     | Contact Email: |

## What Do I Need to Know to Quote or Order a Duct Heater?

| DUCT TYPE                                                                                                      | RECTANGULAR | ROUND    |
|----------------------------------------------------------------------------------------------------------------|-------------|----------|
| Duct Size                                                                                                      | Height      | Diameter |
|                                                                                                                | Width       |          |
| Slip In or Flange Mount                                                                                        |             |          |
| Is the duct internally insulated                                                                               |             |          |
| If so, how thick is the Insulation? <small>Note: Set Recess Equal to the Internal Insulation Thickness</small> |             |          |
| Left Hand or Right Hand Offset Control Box?                                                                    |             |          |
| KW Required                                                                                                    |             |          |
| Voltage Required                                                                                               |             |          |
| Phase Required                                                                                                 |             |          |
| Stages Required                                                                                                |             |          |
| Control Voltage Required                                                                                       |             |          |

### What Accessories or Options are Required?

(See Catalog or Submittal for Details)

|                                                        |                                                             |                                                        |
|--------------------------------------------------------|-------------------------------------------------------------|--------------------------------------------------------|
| <input type="checkbox"/> Gasketed Cover*               | <input type="checkbox"/> Power Fusing (Std. for htrs > 48A) | <input type="checkbox"/> Pilot Light-Heater Energized* |
| <input type="checkbox"/> 80/20 A-Wire                  | <input type="checkbox"/> Fan Interlock Relay*               | <input type="checkbox"/> Pilot Light-Stage Energized*  |
| <input type="checkbox"/> Stainless Steel Terminals     | <input type="checkbox"/> Airflow Switch                     | <input type="checkbox"/> Pilot Light-A.F. Switch Open* |
| <input type="checkbox"/> Vapor Barrier*                | <input type="checkbox"/> Adjustable Airflow Switch*         | <input type="checkbox"/> Disconnect Switch+            |
| <input type="checkbox"/> Derated Coil-35 Watt Density* | <input type="checkbox"/> Transformer                        | <input type="checkbox"/> SCR+                          |
| <input type="checkbox"/> Derated Coil-25 Watt Density* | <input type="checkbox"/> Transformer Fusing-Primary         | <input type="checkbox"/> Electronic Step Controller*+  |
| <input type="checkbox"/> Recessed Terminal Box         | <input type="checkbox"/> Transformer Fusing-Secondary       | <input type="checkbox"/> Room Thermostat               |
| <input type="checkbox"/>                               | <input type="checkbox"/> Time Delay*                        | <input type="checkbox"/> Duct Thermostat               |

\*=Not Available on Round Duct Heaters    +=Not Available on Bottom Mount Duct Heaters

### Custom Build Options:

|                                       |                                         |                                           |
|---------------------------------------|-----------------------------------------|-------------------------------------------|
| <input type="checkbox"/> VAV Heater   | <input type="checkbox"/> Outdoor Rated  | <input type="checkbox"/> Remote Panel     |
| <input type="checkbox"/> Bottom Mount | <input type="checkbox"/> Vertical Mount | <input type="checkbox"/> Plenum Discharge |

### Special Notes/Requirements:

|  |
|--|
|  |
|  |

#### Notes:

1. Please see the installation instructions for installation details and restrictions. 2. For slip in heaters being installed into an internally insulated duct, decrease the height by 2 times the insulation thickness, decrease the width by the insulation thickness, and add a recess equal to the insulation thickness. 3. All heaters will require either a fan relay or an airflow switch per UL requirements. If neither is chosen, a fan relay will be specified. If both a fan relay and airflow switch are required, both must be specified as options/accessories. 4. Power fusing is standard on all heaters above 48.0 amps. Power fusing must be specified as an option/accessory if required for heaters rated 48 amps or less.

Phone: (206) 762 - 0400 | Fax: (206) 763 - 7738 | Email: [quotes@king-electric.com](mailto:quotes@king-electric.com)