

Electric In-Floor Heating Cable





Model Code:

FC 12 120 -3

A: Floor Cable B: 12 - 120V 24 - 240V

C: Watts (120 to 2880)

D: -3 - Includes strapping

In-Floor Heating Cable provides comfort and well-being through radiant heating. Ideal for kitchens & bathrooms.

FC Electric In-Floor Heating Cable Features

- Provides everything needed for easy installation
- 3 Watts/Ft., available in 120V and 240V
- Innovative strapping system included
- 10 Ft. Cold Lead
- Twenty year limited warranty

- No EMF, twin conductor
- Pre-sized kits range from 5 to 320 square feet
- For use with engineered wood, laminate wood, tile, stone floors
- Professional grade quality components
- Phone & email support, online video for easy installation steps
- Tefzel® Insulation, PVC Jacket





	MODEL	UPC	VOLTS	STANDARD (3" SPACING)	(2" SPACING)	(4" SPACING)	WATTS	AMPS	INCLUDED STRAPPING
	FC12120-3	40228	120	10 SQ. FT.	5 SQ. FT.	15 SQ. FT.	120	1.0	10 PCS
	FC12180-3	40229	120	15 SQ. FT.	10 SQ. FT.	20 SQ. FT.	180	1.5	12 PCS
	FC12240-3	40230	120	20 SQ. FT.	15 SQ. FT.	25 SQ. FT.	240	2.0	20 PCS
	FC12300-3	40231	120	25 SQ. FT.	18 SQ. FT.	35 SQ. FT.	300	2.5	20 PCS
	FC12360-3	40232	120	30 SQ. FT.	20 SQ. FT.	40 SQ. FT.	360	3.0	20 PCS
120V	FC12480-3	40233	120	40 SQ. FT.	25 SQ. FT.	55 SQ. FT.	480	4.0	30 PCS
	FC12600-3	40234	120	50 SQ. FT.	35 SQ. FT.	65 SQ. FT.	600	5.0	30 PCS
	FC12720-3	40235	120	60 SQ. FT.	40 SQ. FT.	80 SQ. FT.	720	6.0	40 PCS
	FC12840-3	40236	120	70 SQ. FT.	45 SQ. FT.	95 SQ. FT.	840	7.0	40 PCS
	FC12960-3	40237	120	80 SQ. FT.	55 SQ. FT.	105 SQ. FT.	960	8.0	50 PCS
	FC121080-3	40238	120	90 SQ. FT.	60 SQ. FT.	120 SQ. FT.	1080	9.0	50 PCS
	FC121200-3	40239	120	100 SQ. FT.	65 SQ. FT.	135 SQ. FT.	1200	10.0	60 PCS
	MODEL	UPC	VOLTS	STANDARD (3" SPACING)	(2" SPACING)	(4" SPACING)	WATTS	AMPS	INCLUDED STRAPPING
	FC24240-3	40240	240	20 SQ. FT.	15 SQ. FT.	25 SQ. FT.	240	1.0	20 PCS
	FC24360-3	40241	240	30 SQ. FT.	20 SQ. FT.	40 SQ. FT.	360	1.5	20 PCS
	FC24480-3	40242	240	40 SQ. FT.	25 SQ. FT.	55 SQ. FT.	480	2.0	30 PCS
	FC24600-3	40243	240	50 SQ. FT.	35 SQ. FT.	65 SQ. FT.	600	2.5	30 PCS
	FC24720-3	40244	240	60 SQ. FT.	40 SQ. FT.	80 SQ. FT.	720	3.0	40 PCS
	FC24840-3	40245	240	70 SQ. FT.	45 SQ. FT.	95 SQ. FT.	840	3.5	40 PCS
	FC24960-3	40246	240	80 SQ. FT.	55 SQ. FT.	105 SQ. FT.	960	4.0	50 PCS
	FC241080-3	40247	240	90 SQ. FT.	60 SQ. FT.	120 SQ. FT.	1080	4.5	50 PCS
240V	FC241200-3	40248	240	100 SQ. FT.	65 SQ. FT.	135 SQ. FT.	1200	5.0	60 PCS
	FC241320-3	40249	240	110 SQ. FT.	75 SQ. FT.	145 SQ. FT.	1320	5.5	60 PCS
	FC241440-3	40250	240	120 SQ. FT.	80 SQ. FT.	160 SQ. FT.	1440	6.0	60 PCS
	FC241680-3	40251	240	140 SQ. FT.	95 SQ. FT.	190 SQ. FT.	1680	7.0	70 PCS
	FC241920-3	40252	240	160 SQ. FT.	105 SQ. FT.	210 SQ. FT.	1920	8.0	80 PCS
	FC242160-3	40253	240	180 SQ. FT.	120 SQ. FT.	240 SQ. FT.	2160	9.0	80 PCS
	FC242400-3	40254	240	200 SQ. FT.	135 SQ. FT.	265 SQ. FT.	2400	10.0	90 PCS
	FC242880-3	40390	240	240 SQ. FT.	160 SQ. FT.	320 SQ. FT.	2880	12.0	90 PCS
	MODEL	UPC		ACCESSORIES					
	UDG-4999	33165		Electronic Programmable Floor	Stat with Floor Sense	or, 15 Amp, 5mAA	120/208/	/240V, GI	CI
	FCS11	40088		Heating Cable Monitor		_			

See FC/FCM Accessories page 168 for complete listing of accessories



UDG-4999 Programmable



Floor Sensor Included with Thermostat