



## **SUBMITTAL SHEET**

Job Name:			Submitted By:				Date:	
Location: _								
Architect:								
Engineer:			Approved B	y:		Dat	te:	
Contractor	•							
Submitted	Ву:							
King Conta	ıct:							
Quotes@k	ing-electric.com							
Date:								
Tag	Qty	Item Number	Watts	Volts	PH	Amps	Weight	
	_							
	_							
	_							
	_							
Acces	sories			1	I ———			
Tag	Qty	Item Number						
	-							



# Large Hydronic Heater HL/HLE Series







**Model Code:** 

**IYDRONIC** 

- Tangential blowers
- Fast coil heating
- Quiet operation
- 1/2" trade size copper tubes
- Flow-through design
- 4 or 8 aluminum fins per inch
- Easy motor removal for maintenance
- Permanently lubricated motor
- Powder-coated white or satin black grill
  Use HW series thermostats
- Hi / Off / Lo fan switch
- Aqua Stat included


  - 2-vear limited warrantv

## HL / HLE Series Large Hydronic Heater - 6,700 to 27,250 BTU

King's HL HLE Series large hydronic heater uses the energy from a building's existing hot water source to offer efficient, whisper quiet operation and the ability to reduce utility bills with individual room control. By installing hydronic heaters in every room, you can easily heat only the areas in use and conserve energy. Designed to fit neatly between standard wall study, this in-wall heater provides out of the way positioning ideal for use in public areas, corridors, entry ways and large rooms or hallways. For use in both residential and commercial applications. Provides 6700 to 27,250 BTU heat output. Recommended 17 BTU per square foot for new construction.

istruction.	Model Number	Volts	Can Size	Grill Size	
	HL & HLE 1012 & 1412 – all versions	120	24¾"h <b>x</b> 14 ¼"w <b>x</b> 4¾"d	26¼"h <b>x</b> 15½"w <b>x</b> ¾"d	

			112 G 1122 10 12 G 1 1 12 G 11 10 G 10 10 10 10 12 1			21/11/21/11/21/11/21/21/21/21/21/21/21/2			
MODEL	FT. OF WATER PRESSURE DROP @ 2 GPM	120°F 48°C	140°F* 60°C	160°F* 71°C	180°F 82°C 200°F MAX	Motor Hi/Lo CFM	Decibels at 3-ft distance	Hi/Lo: Amps Hi/Lo: Watts	
HL1012 8/11	.90	6000 BTU 4700 BTU	8550 BTU 6200 BTU	11100 BTU 8000 BTU	14800 BTU 11000 BTU	3 watt output 250 / 150CFM	Hi 57/55 dbA Lo 54/52 dbA	.30 / .29 Amps 36 / 34.8 Watts	
HL1012 10/13	.90	7500 BTU 5500 BTU	10000 BTU 8000 BTU	13500 BTU 9750 BTU	16600 BTU 12000 BTU	3 watt output 250 / 150CFM	Hi 57/55 dbA Lo 54/52 dbA	.30 / .29 Amps 36 / 34.8 Watts	
HL1012-11/15	.90	8812 BTU 6600 BTU	11700 BTU 8800 BTU	15500 BTU 11600 BTU	18700 BTU 14000 BTU	5 watt output 375 / 220 CFM	Hi 64/62 dbA Lo 60/58 dbA	.42 / .38 Amps 50.4 / 45.6 Watts	
HL1412-15/20	1.2	10600 BTU 7400 BTU	15500 BTU 11600 BTU	20000 BTU 15000 BTU	26000 BTU 19500 BTU	5 watt output 375 / 220 CFM	Hi 64/62 dbA Lo 60/58 dbA	.42 / .38 Amps 50.4 / 45.6 Watts	
HL1412-20/25	1.2	17000 BTU 13000 BTU	20000 BTU 16800 BTU	24050 BTU 19100 BTU	27250 BTU 22500 BTU	9 watt output 375 / 220 CFM	Hi 64/62 dbA Lo 60/58 dbA	.42 / .38 Amps 50.4 / 45.6 Watts	
Energy saver ECM Motor	FT. OF WATER PRESSURE DROP @ 2 GPM	120°F 48°C	140°F* 60°C	160°F* 71°C	180°F 82°C	Progressive CFM	Decibels at 3-ft distance	Energy saver Hi/Lo: Amps Hi/Lo: Watts	
HLE 1012-11/15	.90	8812 BTU 6600 BTU	11700 BTU 8800 BTU	15500 BTU 11600 BTU	18700 BTU 14000 BTU	150 to 375 High 150 to 250 Low	Hi 57/55 dbA Lo 54/52 dbA	.06 / .04 Amps 7.2 / 4.8 Watts	
HLE 1412-15/20	1.2	10600 BTU 8812 BTU	15500 BTU 11700 BTU	20000 BTU 15500 BTU	26000 BTU 18700 BTU	150 to 375 High 150 to 250 Low	Hi 63/61 dbA Lo 54/52 dbA	.09 / .06 Amps 10.8 / 7.2 Watts	



BTU ratings based on 68° entering air. To calculate 1 GPM, multiply by 0.95. To calculate 4 GPM, multiply by 1.05.

#### **Replacement Accessories**

ADD SUFFIX:	UPC	DESCRIPTION	WT. (lbs.)
HL GRILL	22209	HL Grill 100-0330	4.9

### **Engineering Specifications**

Contractor shall supply and install H Series hydronic fan heaters manufactured by King Electrical Mfg. Co., Seattle, Washington.

**Motor:** 2 speed shaded pole impedance protected. Permanently lubricated. Bronze bearings.

Blower: Tangential blower to provide 50 or 120 CFM of air. Quiet operation of less than 53 dB A weighted scale at high speed. Easily removed for service. Bronze, not plastic, bearings.

**Coils:** 1/2" ID Copper tubes with Aluminum fins of no more than 8 fins per inch for free flow of air and maximum circulation of air and water. Tested at 300 PSI for leaks. Copper tube used in coil is Alloy 122 made to ASTM B-75 specifications. For potable water use.

Grill: 20 gauge mild Steel, louvered with Nickel-plated grill screws. Powder-coated in white.

**Wall Can:** 20 gauge mild Steel, electro-galvanized to resist corrosion. 1/2" knockout in bottom of can and QuickSet™ bend out mounting tabs for fast installation.

Fan Switch: 3 position fan switch High / Off / Low. Rated at 10 Amps with wire leads and insulated 1/4" quick connects.

**Aqua Stat:** ensures the water temperature is over 115°F before the fan turns ON **Terminal Board:** All electrical connections will terminate at a phenolic terminal board with 1/4" male brass blades for easy wiring.

Water Connections: 1/2" ID bare Copper tubes de-burred. Tested at 300 PSI for leaks. Clean out tubes for water connection.

Approvals: ETL (3131491PRT-001). All King heaters are tested to UL 1995 Standards. Approved for USA and Canada. CSA/C22.2.