

New Product Release







PX EC02S

2-Stage Electronic Heater w/ Remote Temperature Sensing

Selectable Wattages Up To 1750W For Living Spaces

Meet the ECO2S Temperature Sensor.

With the ECO2S Temperature Sensor, your heater knows exactly where the room's cold spot is and works smarter to keep the entire room comfortable. Just place it on a wall or shelf and get the right temperature, right where you want it.











PX ECO2S

2-Stage Electronic Heater w/ Remote

Smart Energy-Saving Design

ECO2S 2-Stage Heating: Automatically Uses Lowest Wattage Needed

Includes ECO2S Remote Temperature Sensor For Balanced Heating

Measures The Temperature At The Exact Spot In The Room Where You Need The Most Comfort, Eliminating Cold Spots

Infrared Remote Control Included

Pic-A-Watt® Element: Multiple Wattage Options, Tailors Heater To Specific Heating Requirements

Patented Smart Limit Protection®



Built-In Fan Delay To Dissipate Heat

Whisper Quiet Squirrel Cage Blower

Timer and Summer Fan Only Modes

Available in New Designer Finishes White Dove, Almondine, Satin Nickel or Oiled Bronze

WARRANTY

5-Year Limited Warranty







New Product Release

Meet the EC02S Temperature Sensor.

With the ECO2S your heater knows exactly where the room's cold spot is and works smarter to keep the entire room comfortable. Just place it on a wall or shelf. Get the right temperature, right where you want it.





Balanced Heat Throughout the Space



Comfort, Right Where You Want It



Remote Temperature Sensing



Modern Curved Grill - Simultaneously makes a bold statement and blends in with any décor

Selectable Wattage – Tailor the heater to an area's specific heating requirements.

ECO2S Electronic Control – Automatically uses lowest wattage needed to heat the room

Infrared Remote Control Included

Timer and Summer Fan Only Modes

ECO2S Remote Temperature Sensor -Temperature Sensing At The Coldest Spot In The Room For Balanced Heating



Ordering Information *Add suffix -AD-R for optional Almondine color -SN-R for optional Satin Nickel color -OB-R for optional Oiled Bronze color

MODEL	COLOR	UPC	VOLTS	WATTS	AMPS	WT. (lbs.)
PX1215-ECO-WD-R	White Dove	17237	120	750•1000•1250•1500	6.25-12.5	12.5
PX2017-ECO-WD-R	White Dove	17238	208*	750•1250•1500•1750	3.6-8.4	12.5
PX2417-ECO-WD-R	White Dove	17239	240	750•1250•1500•1750	3.1-7.3	12.5

