


## Self-Regulating Pipe Trace Cable





## **Model Code:**

12 3 -250 SR A B D A: Self Regulating Cable B: 12 - 120V 24 - 240V C: Watts per foot **D: Linear Length in feet** 

SR Series Self-Regulating Heating Cable is designed for a variety of industrial and commercial pipe trace applications.

## **SR Self-Regulating Heating Cable Features**

Stops pipe and valve freeze down to -40°F

• Cable will not overheat or burn out when overlapped

Suitable for use on metal and plastic pipes 2 year warranty



				AVAILABLE LENG	THS		
	VOLTS	PIPE RATING** WATTS/FT.	100 FT. LENGTH MODEL / UPC	250 FT. LENGTH MODEL / UPC	500 FT. LENGTH MODEL / UPC	1000 FT. LENGTH MODEL / UPC	WEIGHT/FT.
120V	120	3	SR123-100 / 40513	SR123-250 / 40414	SR123-500 / 48735	SR123-1000 / 40416	0.080 LBS./FT.
	120	5	SR125-100 / 40514	SR125-250 / 40418	SR125-500 / 48736	SR125-1000 / 40420	0.080 LBS./FT.
	120	8	SR128-100 / 40515	SR128-250 / 40422	SR128-500/ 48737	SR128-1000 / 40424	0.080 LBS./FT.
	120	10	SR1210-100 / 40516	SR1210-250 / 40426	SR1210-500 / 48742	SR1210-1000 / 40428	0.080 LBS./FT.
	VOLTS	PIPE RATING** WATTS/FT.	100 FT. LENGTH MODEL / UPC	250 FT. LENGTH MODEL / UPC	500 FT. LENGTH MODEL / UPC	1000 FT. LENGTH MODEL / UPC	WEIGHT/FT.
240V	240*	3	SR243-100 / 40517	SR243-250 / 40430	SR243-500 / 48739	SR243-1000 / 40432	0.080 LBS./FT.
	240*	5	SR245-100 / 40518	SR245-250 / 40434	SR245-500 / 48740	SR245-1000 / 40436	0.080 LBS./FT.
	240*	8	SR248-100 / 40519	SR248-250 / 40438	SR248-500 / 48741	SR248-1000 / 40440	0.080 LBS./FT.
	240*	10	SR2410-100 / 40520	SR2410-250 / 40442	SR2410-500 / 48746	SR2410-1000 / 40444	0.080 LBS./FT.

1

\*Approved for 208, 220, 240, 277 volt operation, refer to wattage adjustment tables for output rating. (See Page 191, Table 4) \*\*Wattage rating for pipe freeze protection application is determined at 50°F (10°C).

## Controls and thermostats should always be used with King heating cable systems.

**SR ACCESSORIES** Refer to page ?? for Pipe Freeze Protection Accessories

MODEL	UPC	DESCRIPTION	WEIGHT
SRK00	40462	Hard wired power connection kit, includes end seal	0.3 lbs.
SRK02	40461	Connection kit, includes end seal	0.3 lbs.
SRK03	40464	Pipe trace tape (66 ft) and 10 labels per pack	0.1 lbs.
SRK04	61713	2.5" x 50 yards 2 Mil Foil tape	1.0 lbs.
SRK08	40466	Plug in 120V connection kit with GFEP device, includes end seal	1.0 lbs.
SRK10	40468	Weatherproof splice/tee kit, includes end seal	0.2 lbs.
SRK12	40470	End seal kit (2 per package)	0.1 lbs.
SRK17	40477	11 & 13mm Gel end seal	0.1 lbs.
SRK18	40512	Lighted end seal, 85-277V	0.3 lbs.
IFC12	40490	Plug in fixed thermostat, 120V, 15 amp, on at 35°F off at 45°F (12/case)	0.3 lbs.
TRF-115-005	40477	Freeze protection thermostat, weatherproof with 5ft. remote bulb & capillary, 25 amp at 120/208/240V,	0.3 lbs.

22 amp at 277V, adjustable temp 0°F, suitable for 24 VAC operation (w/Power-On indicator light)