



# SUBMITTAL SHEET

Job Name:	_____	Submitted By:	_____	Date:	_____
Location:	_____		_____		_____
Architect:	_____		_____		_____
Engineer:	_____	Approved By:	_____	Date:	_____
Contractor:	_____		_____		_____
Submitted By:	_____		_____		_____
King Contact:	_____		_____		_____
<a href="mailto:Quotes@king-electric.com">Quotes@king-electric.com</a>					
Date:	_____				

Tag	Qty	Item Number	Watts	Volts	PH	Amps	Weight
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____	_____	_____

## Accessories

Tag	Qty	Item Number
_____	_____	_____
_____	_____	_____
_____	_____	_____

# High Velocity Outdoor Rated Air Circulator WFO Series

Optional Misting Kit  
(Shown)



## Model Code:

WFO -24  
A B

A: Series  
B: Fan Diameter  
-24 = 24"  
-30 = 30"



- 24" & 30" Commercial High Velocity Oscillating Air Circulator
- Outdoor Rated with Wall Mount
- Wall mounted to direct airflow
- 80 degree oscillating motion
- Optional Misting Kit Available
- Optional Fan-Speed-Controller
- 3-Speed Pull Chain Switch
- Totally Enclosed, Outdoor Rated Motor
- 3 Aerodynamically Balanced Blades
- Heavy Duty Steel Fan Guards
- Meets OSHA 1910.212(A)(5) Requirements
- 9 Ft, 120V Grounded Cord & GFCI Plug
- Scratch Resistant, Powder- Coated Finish
- UL Certified for USA & Canada
- 1-Year Limited Warranty

## The King High Velocity Commercial Air Circulator

**King Commercial High Velocity Outdoor Rated Oscillating Air Circulators** are a powerful commercial-grade solution for cooling workshops, warehouses, factories, gyms and more. This oscillating fan motion distributes airflow in a 80 degree sweeping motion or disengage for manual desired hand positioning. The waterproof, totally enclosed motor is outdoor rated for wet locations and offers 3-speeds. Featuring 3 aerodynamically balanced aluminum blades for even, steady airflow and to provide maximum air and motor efficiency. The scratch resistant King green finish looks sharp and is easy to clean. Wall Mounted to direct the air flow where you need it most.

### Ordering Information

MODEL NUMBER	UPC #093319	DESCRIPTION	CFM	WT. (lbs.)
WFO-24	33154	24" Outdoor Rated Oscillating Wall Mounted Air Circulator	7500/6200/4900	38.0
WFO-30	33155	30" Outdoor Rated Oscillating Wall Mounted Air Circulator	8200/6800/5300	42.0

### Accessories

MODEL	UPC	DESCRIPTION	SHIP WEIGHT lbs
PFO-MISTKIT	33153	Add-On Accessory For Optional Misting Feature	0.5
FO-COVER-24	55376	24" Water Resistant Fan Cover	0.25
FO-COVER-30	55377	30" Water Resistant Fan Cover	0.25
FAN-SPEED-CONTROLLER	55378	Fan Motor Variable Speed Control Plug-In, 120V 3A Max	0.5



FAN-SPEED-CONTROLLER



FO-COVERS  
(Available in 24" & 30")

# High Velocity Outdoor Rated Air Circulator WFO Series

## WFO Series



Outdoor Rated  
for Wet Locations

Water Resistant  
Fan Cover  
(Available in 24" & 30")

Oscillating Fan Motion Distributive  
Airflow in a 80 Degree Sweep or  
Disengage for Manual Desired  
Hand Positioning

(3) Non-Corroding  
Aluminum Blades  
for Maximum Airflow

3-Speed Pull Chain  
Switch Controls Air  
Flow Output to  
Match Your Needs

Optional Misting  
Kit Available: Adds  
a Fine Mist of Cool  
Comfort to Hot  
Environments

9 Ft Grounded Three  
Wire Conductor Cord  
& GFCI Plug, 120V -  
For Easy Portability  
& Safety

Wall Mount Bracket

Optional  
PFO-Mistkit

